

Pokini Tab M10

The platform for medical digitalization



Hot-Swap
Akku



Robust and fall re-
sistant



Protection against dust
and jet water



Glove operable



antimicrobial



Pokini Tab M10

Display

| | |
|-------------------|--|
| Size | 10,1" (25,65 cm) |
| Resolution | 1.920 x 1.200 px |
| Typ | IPS panel, capacitive, 10 finger multitouch |
| Brightness | 400 cd/m ² oder 800 cd/m ² |
| Features | <ul style="list-style-type: none">• Dragontrail™ display stable, flexible scratch resistant• Digitizer function |

Technical data

| | |
|-------------------|--|
| OS | Windows® 10 Pro 64-bit |
| CPU | <ul style="list-style-type: none">• Intel® Core™ i5-7Y54 (2x 1,20 GHz up to 3,20 GHz)• Intel® Core™ i7-7Y75 (2x 1,30 GHz up to 3,60 GHz) |
| RAM | up to 16 GB (LPDDR3 PC1866) |
| Storage | up to 1 TB m.2 SSD |
| Kamera | <ul style="list-style-type: none">• front: 2.0 megapixel• rear: 5.0 megapixel |
| Wireless | <ul style="list-style-type: none">• WLAN IEEE 802.11 a/b/g/n/ac• 4G LTE• GPS (u-blox)• Bluetooth 4.2 |
| Sensors | <ul style="list-style-type: none">• Accelerometer• eCompass• Gyrometer• Light Sensor |
| Battery | Lithium-ion battery, approx. 3,700 mAh (hot-swap), up to 9 h runtime |
| Interfaces | <ul style="list-style-type: none">• USB 3.0 Type-A™ (project-based with 2.0 A current)• HDMI• LAN (1 Gbs)• Docking port |

More date

| | |
|----------------------------|--|
| Size | 280 x 256 x 22 mm |
| Weight | approx. 1.100 g |
| Warranty | <ul style="list-style-type: none">• 2 year bring-in (Battery 6 month)• up to 5 years Service Extension (optional) |
| Imagestability | Available until 2024 |
| Optional extensions | <ul style="list-style-type: none">• 1D/2D Barcode Reader• RFID reader• NFC• Smart Card Reader |

Special features

| | |
|---|--|
| Environment | <ul style="list-style-type: none">• Operation: -10 °C to +50 °C• Storage: -20 °C to +60 °C• Humidity: 10% to 90% |
| Protection class & Standards | <ul style="list-style-type: none">• IP65• MIL-STD 810G• EN 60601-1-2 |
| Special Functions | <ul style="list-style-type: none">• Disinfectable• Hot-swap battery function• VESA 75 mounting options• Hard Handle• Fingerprint reader (optional) |

Available accessories

- docking station with 2x USB 3.0, 1x HDMI, 1x slot for battery, 1x RJ45, 1x RS232, DC-IN
- passive pen or digitizer
- car/vehicle cradle, lockable (active)
- display protection foil
- case with 2-point or 4-point shoulder strap